

# DECLARATION OF PERFORMANCE

## 001-DPR-20130701

**ASCOT ARCE 29,4X120(A)**

**1. Unique identification code of the product-type**

Dry pressed ceramic tiles with low water absorption  $E \leq 0.5\%$

**2. Intended uses**

Internal and external walls and floorings

**3. Manufacturer**

PORCELANOSA S.A.  
Ctra .N-340 Km. 56,2  
12540 Vila-real (Castellón)  
SPAIN

**4. System(s) of assessment and verification of constancy of performance (AVCP)**

System 4

**5. Notified laboratory**

Not applicable

**6. Declared performance**

Characteristics	Performance	Harmonised technical specification
Reaction to fire:	A1-A1 :fl	EN 14411 : 2012
Release of dangerous substance:	-	
Cadmium	NPD	
Lead	NPD	
Breaking strength:	$\geq 1300N$	
Slip resistance: (Pendulum method (wet), slider 57, CEN/TS 16165:2012)	NPD	
Tactility:	NPD	
Bond strength/ Adhesion:	-	
Cementitious adhesive, type C2	1,5 N/mm :2	
Reactive resin adhesive	3,1 N/mm :2	
Thermal shock resistance:	Pass	
Durability for:	-	
Internal use	Pass	
External use (Freeze-thaw resistance)	Pass	

\* The performance of the product identified in point 1 is in conformity with the declared performance in point 6

\* This declaration of performance is issued under the sole responsibility of the manufacturer in point 3.

**Name and function:** Manuel Diago García (proxy)

**Place and date of issue:** Vila-real July 1, 2013



**PORCELANOSA, S.A.**