

DDECLARATION OF PERFORMANCE Nº 01DPR20130701 PORCELANICO (STON-KER – PORCELANICO - STARWOOD)

NOA-L TANZANIA ALMOND 59,6X59,6(A)

1. Unique identification code of the product-type

Dry pressed ceramic tiles with low water absorption $E \leq 0.5\%$

2. Intended uses

Internal and external walls and floorings

3. Manufacturer

VENIS S.A.
Ctra .N-340 Km. 56,5
12540 Vila-real (Castellón)
SPAIN

4. System(s) of assessment and verification of constancy of performance (AVCP)

System 4

5. Notified laboratory

Not applicable

6. Declared performance

Characteristics	Performance	Harmonised technical specification
Reaction to fire:	A1-A1 :fl	EN 14411 : 2012
Release of dangerous substance:	-	
Cadmium	NPD	
Lead	NPD	
Breaking strength:	$\geq 1300N$	
Slip resistance: (Pendulum method (wet), slider 57, CEN/TS 16165:2012)	NPD	
Tactility:	NPD	
Bond strength/ Adhesion:	Do not install with cement mortar	
Cementitious adhesive, type C2	1,3 N/mm :2	
Reactive resin adhesive	2,0 N/mm :2	
Thermal shock resistance:	Pass	
Durability for:	-	
Internal use	Pass	
External use (Freeze-thaw resistance)	Pass	

* The performance of the product identified in point 1 is in conformity with the declared performance in point 6

* This declaration of performance is issued under the sole responsibility of the manufacturer in point 3.

Name and function: MANUEL COLONQUES SANZ (proxy)

Place and date of issue: Vila-real July 1, 2013



PORCELANOSA Grupo