

Model: PATAGONIA HOME

Codes: 100000176

Group: G-238

Format: 30X60X1



RECOMMENDATIONS

Recommended adhesive	100031189 SUPER-ONE N GRIS	
Recommended adhesive (wet area)	100031189 SUPER-ONE N GRIS	
Recommended joint	100236481 COLORSTUK RAPID ANTRACITA N	
Recommended joint (wet area)	100236481 COLORSTUK RAPID ANTRACITA N	100086920 FILA FOB EXTREME

ADDITIONAL NOTES

Due to the texture of the slates, it is important that when they are grouted we try to cover the least amount of the pieces so as to make subsequent cleaning easier and prevent the joint from staying between the different textures.

TOLERANCES

Indoor tolerance	±4 mm (ancho), ±4 mm (largo), ±3 mm (espesor)	UNE-EN 1341:2013*
Outdoor tolerance	±4 mm (ancho), ±4 mm (largo), ±3 mm (espesor)	UNE-EN 1341:2013*

LABORATORY TESTS

Bulk density	2820 Kg/m ³	UNE EN 1936:2007*
Flammability	A1f l/A1	UNE-EN 13501-1:2007+A1:2010*
Flexural strength	35 MPa	UNE-EN 12372:2007*
Frost resistance	31.5 MPa	UNE-EN 12371:2011*
Resistance to abrasion (except g.7-8)	18 mm	UNE-EN 14157:2005*
Resistance to thermal shock	-0.03%/7.9%	UNE -EN 16140:2011*
Slip resistance	37/61	UNE-EN 14231:2004*
Slip resistance (dcof)	0.38	ASTM C1028*
Water absorption at atmospheric pressure	0.21%	UNE-EN 13755:2002*

FEATURES

- Protection that reduces the appearance of the most common domestic bacteria.
- There are slight color changes between pieces.
- Material from an American country.
- Material suitable for use on indoor walls.
- Material suitable for use on bathroom countertops.
- Material suitable for use on shower walls.
- Material suitable for use on outdoor walls.
- Material that stands out for having an asymmetrical surface.
- Material suitable for use on indoor floors.



PACKING

Base unit	PIECES	
Boxes	0.72 M2/BOX	
Gross weight	27.4889 KG/M2	
Net weight	26.7944 KG/M2	
Pallets	31.68 M2/PAL	
Sale unit	M2	
Units	0.18 M2/PIECE	

