

Model: COLORSTUK ESPECIAL WHITE

Codes: 100090690



### GENERAL FEATURES

Family	COLORSTUK SPECIAL	
Installation	WALL TILES/FLOOR TILES	
Ceramic wall	MOSAIC WALL TILES	
Ceramic wall	RECTIFIED WALL TILES	
Ceramic wall	GLOSSY WALL TILES (CRYSTAL)	
Ceramic wall	WALL TILES	
Ceramic wall	NATURAL STONE	
Ceramic wall	PAR-KER	
Ceramic wall	GLASS MOSAIC	
Ceramic wall	STON-KER	
Ceramic wall	URBATEK	
Ceramic wall	POLISHED URBATEK	
Ceramic wall	XLIGHT	
Ceramic floor	STON-KER	
Ceramic floor	NATURAL STONE	
Ceramic floor	PORCELAIN FLOOR TILES	
Ceramic floor	STONEWARE FLOOR TILES	
Ceramic floor	PAR-KER	
Ceramic floor	GLASS MOSAIC	
Ceramic floor	URBATEK	
Ceramic floor	POLISHED URBATEK	

Follow the installation and maintenance instructions published and recommended by PORCELANOSA GRUPO, adhering to the legal or regulatory requirements existing on each region.

Do not use cleaning agents containing hydrofluoric acid.

In public spaces, tiles must comply with the anti-slip rating under the DCOF (dynamic coefficient of friction) standards.

For big sizes, it is recommended using flexible modified adhesives applied by back-buttering.

This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by BUTECH S.A.U.

Being the ceramic material that most resembles natural stone, it can show slight variations in shade, color spots and vein among pieces.