

Model: AUTHENTIC 1L CHROME  
Codes: 100171977 - L165003580  
Group: G-265  
Format: 24X220X1,35



### ADDITIONAL NOTES

Due to better usage of the wood, any order of this reference may contain mean percentage boards of between 20% y 25%.

### COMPOSITION



	Size	Material	Type of material
Layer 1	0.060-0.070	Oil	Natur Plus treatment
Layer 2	3.5	Hardwood Layer	Madera de Roble
Layer 3	10	Intermediate Layer	Softwood veneer

### LABORATORY TESTS

Flammability	Dfl-s1	EN 13501*
Formaldehyde emissions	E1	EN 717*
Gluing resistance	≥D3	DIN EN 204*
Heat resistance	0.09 M2**K/W	UNE-EN 12667:2002*
Mass per surface	7.41 KG/M2	EN 14342*
Moisture content	7.00%	UNE-EN 13183-1/AC:2004*
Resistance to chair castors	No damage	DIN EN 425*
Thermal conductivity	0.133 W/M**K	UNE-EN 12667:2002*

## FEATURES

- 

It is one of the easiest to install and safest systems in the market. We just need to adjust the board to be installed longitudinally to the one already placed, by applying a soft pressure without the need for any type of tool. Both pieces will fit and will be secured thanks to the safety tab. It is just as simple to take apart, which makes for a quick disassembly.
- 

Slight smoothing of the wood using a brush to achieve a surface with a slight relief.
- 

Combination of oils and waxes prepared for drying with UV lamps. With this finish, wood preserves the natural look of conventional oil but is more resistant to stains from everyday-use products and needs less maintenance. Advantages: Very natural look, low maintenance, and greater resistance to stains from water, wine, juice... Right after installing and before its first use we recommend the use of CLEAN&GREEN AQUA OIL 1 L.
- 

Is suitable for installing on water radiant heating.
- 

Material with many knots on its surface that can have different sizes depending on the type of wood. These, along with any cracks that may appear, are covered with putty.
- 

It is necessary to apply adhesive for installing it.
- 

There are consistent color changes between pieces.
- 

Material from a European country.
- 

Structure formed by an upper layer that shows the noble aspect of the material, an intermediate layer of wood of different typology, depending on the collection, or HDF board that compensates the tensions between the different parts and a lower plywood that provides dimensional stability.
- 

Applying a color oil or varnish on the wood surface in order to get different color ranges.
- 

Beveled cut on all 4 edges of the board for emphasizing size.
- 

Quality product made with selected raw materials, guaranteeing its full residential use for 30 years as provided by L' Antic Colonial.
- 

Format where only one board has been used to finish the entire base surface.
- 

Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.
- 

Made with oak wood.
- 

Material from a North American country.
- 

PanEuropean Forest Certification that guarantees to consumers the origin of the products from sustainably managed forests.
- 

3.5 mm

## PACKING

Base unit	PIECES
Boxes	3.168 M2/BOX
Gross weight	7.6515 KG/M2
Net weight	7.5758 KG/M2
Pallets	104.544 M2/PAL
Sale unit	M2
Square meters	1 M2

## SPECIAL PIECES

SAP	KEA	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net Weight	Gross weight
100229329	L165004304	IGUALACION AUTHENTIC CHROME 4,5X270X1,3	G-161	10 ST/CS	1000 ST/PAL	9.26 ST/M2	ST	ST	1 KG/ST	1.02 KG/ST
100176728	L165003714	MAMPERLAN AUTHENTIC 1L CHROME 120X7X3	G-163	2 ST/CS	200 ST/PAL	11.9 ST/M2	ST	ST	1.58 KG/ST	1.64 KG/ST
100229372	L165004303	TRANSICION AUTHENTIC CHROME 4X270X1,3	G-161	10 ST/CS	1000 ST/PAL	9.26 ST/M2	ST	ST	1 KG/ST	1.02 KG/ST
100177660	L165003731	ZOCALO AUTHENTIC CHROME 8X220X1,4	G-128	12 ST/CS	600 ST/PAL	5.68 ST/M2	ST	ST	2.58 KG/ST	2.6 KG/ST