

Model: MANHATTAN COGNAC 19,3X120(A)

Codes: 100190027

Water absorption: Bla - Porcelánico (E<=0.1%)



MATE / MATT



RECTIFICADO
TONE VARIATIONS



RECTIFICADO
RECTIFIED



DIMENSIONAL FEATURES

UNE-EN ISO 10545-2

| | | |
|-----------------------------|-------------|----------|
| Length | 1200 MM | |
| Length and width deviation | Below 0.15% | +/-0.3%* |
| Side straightness deviation | Below 0.15% | +/-0.3%* |
| Squareness deviation | Below 0.15% | +/-0.3%* |
| Surface flatness deviation | Below 0.15% | +/-0.4%* |
| Thickness | 11.5 MM | +/-5%* |
| Width | 193 MM | |

*ISO-13006:2018 UNE-EN 14411:2016

MECHANICAL FEATURES

UNE-EN ISO 10545-4-6-7-11

| | | |
|---------------------|------------------|------------|
| Abrasion resistance | 3 - 600 Rev. | |
| Breaking strength | 3677 N | >1300N* |
| Crazing resistance | Resists 3 cycles | |
| Modulus of rupture | 54 N/MM2 | >=35N/mm2* |

*ISO-13006:2018 UNE-EN 14411:2016

HYGIENIC FEATURES

UNE-EN ISO 10545-13-14:1995

| | | |
|---------------------|--|---------|
| Chemical resistance | Class "A" for swimming pools and cleaning products (resists attack). Minimum Class "B" for acids and bases | B Min.* |
| Stain resistance | Class 5. Easy cleaning with water | 3 Min.* |

*ISO-13006:2018 UNE-EN 14411:2016

SCOPE OF USE

| | | |
|------------------|------------------------------|--|
| Technical code-1 | Use on medium traffic floors | |
|------------------|------------------------------|--|

ANTI-SLIP VALUE

UNE 41901:2017 EX, UNE 41902:2017 EX, DIN-51130 y ASTM C1028

| | | |
|---------------------------------|-----------------|--|
| 4s | WET-41 / DRY-60 | |
| Dynamic coefficient of friction | 0.63 | |
| Slip resistance (pendulum-wet) | CL1 | |

*ISO-13006:2018 UNE-EN 14411:2016

System Certification



PACKING

| | | |
|---------|-----------------|--|
| Boxes | 1.158 M2/BOX | |
| Pallets | 55.5839 M2/PAL | |
| Units | 0.2316 M2/PIECE | |

System Certification

