

Model: NOA-L TANZANIA ALMOND 59,6X59,6(A)

Codes: 100202114 - V55907441

Water absorption: Bla - Porcelanico (E<=0.1%)

Thickness: 10.5 mm



DIMENSIONAL FEATURES

UNE-EN ISO 10545-2

Length	596 MM	
Length and width deviation	Below 0.15%	+/-0.3%*
Side straightness deviation	Below 0.15%	+/-0.3%*
Squareness deviation	Below 0.15%	+/-0.3%*
Surface flatness deviation	Below 0.15%	+/-0.4%*
Thickness	10.5 MM	+/-5%*
Width	596 MM	

*ISO-13006:2018 UNE-EN 14411:2016

MECHANICAL FEATURES

UNE-EN ISO 10545-4-6-7-11

Abrasion resistance	3 - 600 Rev.	
Breaking strength	2578 N	>1300N*
Crazing resistance	Resists 3 cycles	
Modulus of rupture	49.7142857142857 N/MM2	>=35N/mm2*

*ISO-13006:2018 UNE-EN 14411:2016

HYGIENIC FEATURES

UNE-EN ISO 10545-13-14:1995

Chemical resistance	Class "A" for swimming pools and cleaning products (resists attack). Minimum Class "B" for acids and bases	B Min.*
Stain resistance	Class 5. Easy cleaning with water	3 Min.*

*ISO-13006:2018 UNE-EN 14411:2016

SCOPE OF USE

Technical code-1	Use on medium traffic floors	
------------------	------------------------------	--

ANTI-SLIP VALUE

UNE 41901:2017 EX, UNE 41902:2017 EX, DIN-51130 y ASTM C1028

Slip resistance (dcof)	0,60	
------------------------	------	--

*ISO-13006:2018 UNE-EN 14411:2016

PACKING

Boxes	1.4209 M2/BOX	
Pallets	45.4675 M2/PAL	
Units	0.3552 M2/PIECE	

System Certification

