

Model: AC5 HELVETIA 1L LINKHAMM

Codes: 100226676 - L167012950

Group: G-204

Format: 19,2X128,5X0,8

Thickness: 8 mm














COMPOSITION



	Size	Material	Type of material
Layer 1		Overlay	Aminoplastic thermosetting resins
Layer 2		Decorative paper	
Layer 3		HDF	High-density Fiber Board and water-repellent glues
Layer 4		Counterbalance	Sheets of kraft paper impregnated with phenolic resins

FEATURES

-  Imitates the surface of wood
-  Installation system where gluing the boards to the floor is not necessary. They are installed on a foam and joined together
-  20 20 year warranty for domestic use valid for laminate floors that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with EN 13329.
-  Is suitable for installing on water radiant heating
-  PanEuropean Forest Certification that guarantees to consumers the origin of the products from sustainably managed forests
-  23. Intensive residential
-  ACS Abrasion-resistance level as per Standard UNE-EN 13329
-  Beveled cut on all 4 edges of the board for emphasizing size
-  5 5 year warranty for commercial use valid for laminate floors that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with EN 13329.
-  Format where only one board has been used to finish the entire base surface
-  Floor capable of dissipating excess electrical charges and distribute them over its entire surface
-  It is a quick and easy installation system. Adjust the slat to be installed lengthwise to the one already placed and tap it lightly with a rubber hammer and block. It is just as easy to uninstall, which allows it to be quickly dismantled.
-  33. Intensive commercial

DIMENSIONAL FEATURES

Difference in height among items	Promedios≤0.1 mm; Máx.Mín≤0.15 mm	EN 13329*
Dimensional variations related to changes in relative moisture	≤0.90 mm	EN 13329*
Flatness of item (f)	f _w ,Cóncavo≤0.50% f _w ,Convexo≤1%/f _l ,Cóncavo≤0.15% f _l ,Convexo≤0.20%	EN 13329*
Item thickness	≤0.50 MM	EN 13329*
Length of face	≤0.9 MM	EN 13329*
Punching	≤0.05 MM	EN 13329*
Squareness of the item (q)	Promedios≤0.1 mm; Máximo 0.15 mm	EN 13329*
Straightness of face	≤0.25 MM	EN 13329*
Surface stripping	≥1.00 N/MM2	EN 13329 Anexo D*
Uv light fastness	≥Grado 4 en escala de grises;≥Grado 6 en escala de azules	EN 20105*
Width of face	≤0.9 mm	EN 13329*

LABORATORY TESTS

Castor chair effect	No damage	EN 425*
Density of the board	950±5 KG/M3	EN 323:1994*
Evaluation of propensity to accumulation of electrostatic charges	≤2 kV	EN 1815*
Fire resistance	Cfl-s1	EN 13501*
Formaldehyde emissions	E1	EN 717*
Furniture leg effect	No damage	EN 424*
Heat resistance	0.073 (m²K)/W ±15%	EN 12667*
Impact resistance	IC2	EN 13329*
Resistance to abrasion	AC5	UNE EN 13329:2000*
Resistance to cigarette burns	Grado 4	EN 438-2.19*
Resistance to staining	Grado 5 (G 1 y 2) y Grado 4 (G 3)	EN 438*
Slip resistance (cls)	clase 1	EN 12633*
Slip resistance (dcof)	Class DS:≥0.30	EN 13893*
Swelling in thickness	≤15%	EN 13329*
Tensile strength of joints	length≥1 kN/m · width≥2 kN/m	EN 13329*
Thermal conductivity	0.110 W/(m*K) ±15%	EN 12664*

PACKING

Base unit	PIECES	
Boxes	2.2205 M2/BOX	
Gross weight	7.9523 KG/M2	
Net weight	7.7618 KG/M2	
Pallets	115.465 M2/PAL	
Sale unit	M2	
Square meters	1 M2	
Units	0.2467 M2/PIECE	

SPECIAL PIECES

SAP	KEA	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net Weight	Gross weight
100228924	L167012998	IGUALACION HELVETIA 1L LINKHAMM 4X270X1	G-155	20 ST/CS	1000 ST/PAL	9.26 ST/M2	ST	ST	0.7 KG/ST	0.72 KG/ST
100228975	L167012980	MAMPERLAN AC5 HELVETIA 1L LINKHAMM 120X7	G-163	2 ST/CS	200 ST/PAL	11.9 ST/M2	ST	ST	1.58 KG/ST	1.64 KG/ST
100228934	L167012989	TRANSICION HELVETIA 1L LINKHAMM 4X270X1	G-155	20 ST/CS	1000 ST/PAL	9.26 ST/M2	ST	ST	0.7 KG/ST	0.72 KG/ST
100228898	L167012979	ZOCALO HELVETIA 1L LINKHAMM 8X220X1,5	G-107	14 ST/CS	560 ST/PAL	5.68 ST/M2	ST	ST	1.8 KG/ST	1.86 KG/ST