

Model: DIP LIGHT Codes: 100226721 Group: G-104

Format: 31,6X31,6X0,4



	RECOMMENDATIONS	
Recommended adhesive	100201526 ONE-FLEX PREMIUM BLANCO	
Recommended adhesive (wet area)	100217753 POLITECH PREMIUM COMP. A+B	
Recommended joint	100236463 COLORSTUK RAPID BLANCO N	
Recommended joint (wet area)	100236463 COLORSTUK RAPID BLANCO N	

TECHNICAL INFORMATION		
Flammability	Afl-s1	EN 13501*
Frost resistance	OK	UNE EN ISO 10545-12*
Resistance to chemicals	SIN EFECTO VISIBLE	UNE EN ISO 10545-13*
Slip resistance (dcof)	0.17	ASTM A137.1*
Slip resistance (pendulum-dry)	CL 3	
Slip resistance (pendulum-wet)	CL 1	
Stain resistance	CLASE 5	UNE EN ISO 10545-14*
Water absorption	0%	UNE EN ISO 10545-3*

FEATURES



Product manufactured on a mesh that makes installation easier.



Material suitable for use on permanently wet areas.



Material suitable for use on shower walls.



Material with surface with the ability to produce reflections.



Material suitable for use on indoor floors.



Material suitable for use on indoor walls.

	PACKING
Base unit	PIECES
Boxes	20 PIECES/BOX
Gross weight	0.879 KG/PIECES
Net weight	0.849 KG/PIECES
Sale unit	PIECES
Square meters	10.0144 PIECES/M2
Units	1 PIECES





It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A.U., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive agents, such as acids or solvents, or metallic or sharp elements for cleaning. In public places mosaics must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.U.