


Model: IMPERIAL 1L NATURAL  
Codes: 100238218 - L165004316  
Group: G-260  
Format: 24X220X1,35  
Thickness: 13.5 mm



### COMPOSITION





	Size	Material	Type of material
Layer 1	0.060-0.070	Varnish	Apresto Mate treatment
Layer 2	3.5	Hardwood Layer	
Layer 3	8.5	Intermediate Layer	
Layer 4	1.5	Backside	Coniferous wood


### LABORATORY TESTS


Biological durability	Clase 1	UNE EN 335 -1 ; UNE EN 335-2*
Bulk density	740 Kg/m <sup>3</sup>	UNE-EN 323:1994*
Critical radiant flux	0.41 W/CM <sup>2</sup> (Class II)	ASTM E648*
Flammability	Cfl-S1	EN 13501-1*
Formaldehyde emissions	≤0.05 ppm (E1)	EN 717-1*
Gluing resistance	≥D3	EN 204*
Heat resistance	0.110 M <sup>2</sup> *K/W	UNE-EN 12667:2002*
Mass per surface	7.41 KG/M <sup>2</sup>	
Moisture content	5-9%	EN 13489*
Resistance to chair castors	> 25000 ciclos	EN 425*
Slip resistance	25/47	UNE-CEN/TS 15676:2008*
Thermal conductivity	0.12 W/M**K	UNE-EN 12667:2002*


## FEATURES


- 


It is one of the easiest to install and safest systems in the market. We just need to adjust the board to be installed longitudinally to the one already placed, by applying a soft pressure without the need for any type of tool. Both pieces will fit and will be secured thanks to the safety tab. It is just as simple to take apart, which makes for a quick disassembly
- 


Slight smoothing of the wood using a brush to achieve a surface with a slight relief.
- 


L'ANTIC COLONIAL's varnishing, in two finishes, APRESTO (gloss) and APRESTO MATE (matte), provides a unique surface quality that satisfies the most demanding requirements. Advantages: It achieves the highest cleanliness because, since the pores are seal...
- 


Is suitable for installing on water radiant heating
- 


Material with many knots on its surface that can have different sizes depending on the type of wood. These, along with any cracks that may appear, are covered with putty.
- 


Installation system where gluing the boards to the floor is not necessary. They are installed on a foam and joined together
- 


There are consistent color changes between pieces.
- 


PanEuropean Forest Certification that guarantees to consumers the origin of the products from sustainably managed forests
- 


Noble layer
- 


Applying a color oil or varnish on the wood surface in order to get different color ranges.
- 


Beveled cut on the long sides of the board in order to create a continuity effect
- 

Quality product made with selected raw materials, guaranteeing its full residential use for 30 years as provided by L' Antic Colonial.
- 

Format where only one board has been used to finish the entire base surface
- 

It is necessary to apply adhesive for installing it.
- 

Made with oak wood.
- 

Material from a European country.
- 

Structure formed by an upper layer that shows the noble aspect of the material, an intermediate layer of wood of different typology, depending on the collection, or HDF board that compensates the tensions between the different parts and a lower plywood that provides dimensional stability.

## PACKING

Base unit	PIECES	
Boxes	3.168 M2/BOX	
Gross weight	8.4754 KG/M2	
Net weight	8.0133 KG/M2	
Pallets	104.544 M2/PAL	
Sale unit	M2	
Square meters	1 M2	

## SPECIAL PIECES

SAP	KEA	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net Weight	Gross weight
100228881	L165004247	IGUALACION IMPERIAL NATURAL 4,5X270X1,3	G-161	10 ST/CS	1000 ST/PAL	9.26 ST/M2	ST	ST	1 KG/ST	1.02 KG/ST
100228907	L165004255	MAMPERLAN IMPERIAL NATURAL 120X7X3	G-163	2 ST/CS	200 ST/PAL	11.9 ST/M2	ST	ST	1.58 KG/ST	1.64 KG/ST
100228890	L165004248	TRANSICION IMPERIAL NATURAL 4X270X1,3	G-161	10 ST/CS	1000 ST/PAL	9.26 ST/M2	ST	ST	1 KG/ST	1.02 KG/ST
100228860	L165004209	ZOCALO IMPERIAL NATURAL 8X220X1,4	G-128	12 ST/CS	600 ST/PAL	5.68 ST/M2	ST	ST	2.58 KG/ST	2.6 KG/ST