

Model: METROPOLITAN NATURE CALIZA 33,3X59,2(A)
Codes: 100243405 - V13498901
Water absorption: BIII - Revestimiento (10%≤E≤20%)
Thickness: 5/16" approx.



DIMENSIONAL FEATURES

| | | |
|-----------------------------|----------------|----------|
| Thickness | 5/16" approx | +/-5%* |
| Width | 13 1/8" approx | |
| Length | 23 1/4" approx | |
| Length and width deviation | Below 0.15% | +/-0.3%* |
| Side straightness deviation | Below 0.15% | +/-0.3%* |
| Squareness deviation | Below 0.15% | +/-0.3%* |
| Surface flatness deviation | Below 0.15% | +/-0.4%* |

*ASTM C485/C499/C502

MECHANICAL FEATURES

| | | |
|---------------------|------------------|----------|
| Breaking strength | 241.32 LBF | >135LBF* |
| Modulus of rupture | 5.11 LBF | >=3LBF* |
| Abrasion resistance | No Aplica | |
| Crazing resistance | Resists 3 cycles | |

*ASTM C648

HYGIENIC FEATURES

| | | |
|---------------------|--|---------|
| Chemical resistance | Class "A" for swimming pools and cleaning products (resists attack). Minimum Class "B" for acids and bases | B Min.* |
| Stain resistance | Class 5. Easy cleaning with water | 3 Min.* |

*ASTM C650/C1378

SCOPE OF USE

| | | |
|------------------|--------------|--|
| Technical code-1 | Use on walls | |
|------------------|--------------|--|

ANTI-SLIP VALUE

| | | |
|---------------------------------|-----------|--|
| Dynamic coefficient of friction | No Aplica | |
| Slip resistance (bare feet) | No Aplica | |

*ANSI A137.1

PACKING

| | | |
|---------|----------------|--|
| Boxes | 12.73 SQF/CS | |
| Pallets | 611.13 SQF/PAL | |
| Units | 2.12 SQF/ST | |

System Certification

