

Model: AC5 CEMENT 1L DARK

Codes: 100244845

Group: G-222

Format: 60,1X118,3X0,8



### ADDITIONAL NOTES

High resistance to water and moisture as long as the instructions for installation of this product for these cases are followed.

### FEATURES

-  Beveled cut on all 4 edges of the board for emphasizing size
-  5 year warranty for commercial use valid for laminate floors that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with EN 13329.
-  Format where only one board has been used to finish the entire base surface
-  Floor capable of dissipating excess electrical charges and distribute them over its entire surface
-  Safety and joint durability are the main features of this easy installation system that guarantees the elimination of gaps between boards throughout the floor's lifetime. The pressure exerted between boards reinforces the union and prevents it from being carried out incorrectly.
-  33. Intensive commercial
-  Suitable for bathroom and kitchen floors for residential use, provided that the product's installation instructions are always followed.
-  Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.
-  25 year warranty for domestic use valid for laminate floors that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with EN 13329.
-  Is suitable for installing on water radiant heating
-  PanEuropean Forest Certification that guarantees to consumers the origin of the products from sustainably managed forests
-  23. Intensive residential
-  ACS Abrasion-resistance level as per Standard UNE-EN 13329

### DIMENSIONAL FEATURES

Difference in height among items	medio≤0.10 mm; max≤0.5 mm	UNE EN 13329*
Dimensional variations related to changes in relative moisture	medio≤0.9 mm-max≤0.9 mm	UNE EN 13329*
Flatness of item (f)	Transversal: cóncava≤0.15%-convexa≤0.20%/Longitudinal: cóncava≤0.5%-convexa≤1%	UNE EN 13329*
Item thickness	≤0.50 del valor nominal MM	UNE EN 13329:2016*
Joint between items	Medio≤0.15 mm; max≤0.20 mm	UNE EN 13329*
Squareness of the item (q)	max≤0.20 mm	UNE EN 13329*
Straightness of face	max≤0.30 mm	UNE EN 13329*
Surface stripping	≥1.25	UNE EN 13329*
Uv light fastness	Grado 4 en escala de grises	EN 20105-A02*
Width of face	Δ≤0.10 mm del valor nominal/max-mins≤0.20 mm	UNE EN 13329*



## LABORATORY TESTS

Evaluation of propensity to accumulation of electrostatic charges	≤2 kV	EN 1815*
Fire resistance	Bfl-s1	EN 13501*
Formaldehyde emissions	E1	EN 712-2*
Impact resistance	CLASE IC3	EN13329 tabla 2*
Moisture upon leaving factory	Entre 4 Y 10%	
Resistance to abrasion	AC5	UNE EN 13329:2000*
Resistance to staining	Grupo 1-2≥5/Grupo 3≥4	EN-438-2 / EN 13329*
Slip resistance (cls)	Húmedo: Clase 1/Seco: Clase 3	UNE-ENV 12633*
Swelling in thickness	≤10%	EN 13329*
Tensile strength of joints	F≥1 kN/ml	UNE EN 13329*

## PACKING

Base unit	PIECES	
Boxes	2.1329 M2/BOX	
Gross weight	9.2745 KG/M2	
Net weight	8.9411 KG/M2	
Pallets	145.0405 M2/PAL	
Sale unit	M2	
Square meters	1 M2	
Units	0.711 M2/PIECE	

## SPECIAL PIECES

SAP	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net Weight	Gross weight
100245107	IGUALACION CEMENT 1L DARK 4X270X1	G-155	20 PIECES/BOX	1000 PIECES/PAL	9.26 PIECES/M2	PIECES	PIECES	0.7 KG/PIECES	0.72 KG/PIECES
100245141	MAMPERLAN AC5 CEMENT 1L DARK 7X120X3	G-163	2 PIECES/BOX	200 PIECES/PAL	11.9 PIECES/M2	PIECES	PIECES	1.58 KG/PIECES	1.64 KG/PIECES
100245098	TRANSICION CEMENT 1L DARK 4X270X1	G-155	20 PIECES/BOX	1000 PIECES/PAL	9.26 PIECES/M2	PIECES	PIECES	0.7 KG/PIECES	0.72 KG/PIECES
100245099	ZOCALO CEMENT 1L DARK 8X220X1,5	G-107	14 PIECES/BOX	560 PIECES/PAL	5.68 PIECES/M2	PIECES	PIECES	1.8 KG/PIECES	1.86 KG/PIECES

