

Model: AC5 CROSS LUXOR CREAM

Codes: 100245567 - L167013169

Group: G-219

Format: 39,42X118X0,8



COMPOSITION



	Size	Material	Type of material
Layer 1	0.06	Overlay	
Layer 2	0.1	Decorative paper	
Layer 3	7.7	HDF Extreme	
Layer 4	0.14	Backside	Kraft counterbalance

ADDITIONAL NOTES

High resistance to water and moisture as long as the instructions for installation of this product for these cases are followed.

FEATURES

- Imitates the surface of wood
- Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.
- 25 year warranty for domestic use valid for laminate floors that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with EN 13329.
- Is suitable for installing on water radiant heating
- PanEuropean Forest Certification that guarantees to consumers the origin of the products from sustainably managed forests
- 23. Intensive residential
- Abrasion-resistance level as per Standard UNE-EN 13329
- Gloss-free
- 5 year warranty for commercial use valid for laminate floors that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with EN 13329.
- 5° 5-year warranties on laminate models installed for residential use that are listed as suitable for bathrooms and kitchens.
- Floor capable of dissipating excess electrical charges and distribute them over its entire surface
- Safety and joint durability are the main features of this easy installation system that guarantees the elimination of gaps between boards throughout the floor's lifetime. The pressure exerted between boards reinforces the union and prevents it from being carried out incorrectly.
- 33. Intensive commercial
- Suitable for bathroom and kitchen floors for residential use, provided that the product's installation instructions are always followed.

DIMENSIONAL FEATURES

Item thickness	≤0.50 del valor nominal MM	UNE EN 13329:2016*
Length of face	≤1500: Δl≤0.5 mm	UNE EN 13329:2016*
Uv light fastness	≥Grado 4 en escala de grises	EN 20105-A02*



LABORATORY TESTS

Acoustic insulation	$\Delta L_w=17$ dB	ISO 10140*
Density of the board	940 \pm 5 KG/M3	UNE EN 323*
Evaluation of propensity to accumulation of electrostatic charges	≤ 2 kV	EN 1815*
Fire resistance	Bfl-s1	EN 13501*
Formaldehyde emissions	E1	EN 717-2*
Impact resistance	CLASE IC3	EN13329 tabla 2*
Residual footprint	≤ 5 MM	EN ISO 24343-1*
Resistance to abrasion	AC5	UNE EN 13329:2000*
Resistance to staining	Grupo 1-2 \geq 5/Grupo 3 \geq 4	EN-438-2 / EN 13329*
Slip resistance (cls)	Húmedo: Clase 1/Seco: Clase 3	UNE-ENV 12633*
Slip resistance (dcof)	0.52	UNE EN 13893*
Swelling in thickness	$\leq 10\%$	EN 13329*
Tensile strength of joints	F ≥ 1 kN/ml	EN 13329*

PACKING

Base unit	PIECES
Boxes	2.3258 M2/BOX
Gross weight	8.7154 KG/M2
Net weight	8.4918 KG/M2
Pallets	97.6828 M2/PAL
Sale unit	M2
Square meters	1 M2
Units	0.4652 M2/PIECE

SPECIAL PIECES

SAP	KEA	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net Weight	Gross weight
100245532	L167013158	IGUALACION CROSS LUXOR CREAM 4X270X1	G-155	20 ST/CS	1000 ST/PAL	9.26 ST/M2	ST	ST	0.7 KG/ST	0.72 KG/ST
100245570	L167013160	MAMPERLAN AC5 CROSS LUXOR CREAM 120X7	G-163	2 ST/CS	200 ST/PAL	11.9 ST/M2	ST	ST	1.58 KG/ST	1.64 KG/ST
100245555	L167013161	TRANSICION CROSS LUXOR CREAM 4X270X1	G-155	20 ST/CS	1000 ST/PAL	9.26 ST/M2	ST	ST	0.7 KG/ST	0.72 KG/ST
100245549	L167013167	ZOCALO CROSS LUXOR CREAM 8X220X1,5	G-107	14 ST/CS	560 ST/PAL	5.68 ST/M2	ST	ST	1.8 KG/ST	1.86 KG/ST

