

Model: WALD 1L CUSTOM SUPREME DUPPEL

Codes: 100253205

Group: G-285

Format: 30X400X1,9



COMPOSITION



	Size	Material	Type of material
Layer 1	0.060-0.070	Oil	Natur treatment
Layer 2	5	Hardwood Layer	Madera de Roble
Layer 3	9	Intermediate Layer	Madera de Hevea / Roble
Layer 4	5	Backside	Madera de Roble

LABORATORY TESTS

Biological durability	Clase 2	UNE EN 335 -1 ; UNE EN 335-2*
Bulk density	690 KG/M3	UNE-EN 323:1994*
Flammability	Cfl-s1	EN 13501*
Formaldehyde emissions	E1	EN 717*
Heat resistance	0.11 M2**K/W	UNE-EN 12667:2002*
Thermal conductivity	0.170 W/M**K	UNE-EN 12667:2002*

FEATURES

- This installation system consists in assembling the boards with slots and cuts on their edges by applying a slight pressure on the boards. The boards are then bonded with white glue. Tools are needed for the installation.
- Beveled cut on all 4 edges of the board for emphasizing size
- Quality product made with selected raw materials, guaranteeing its full residential use for 30 years as provided by L' Antic Colonial.
- Format where only one board has been used to finish the entire base surface
- It is necessary to apply adhesive for installing it.
- There are considerable color changes between pieces.
- Structure formed by an upper layer that shows the noble aspect of the material, an intermediate layer of wood of different typology, depending on the collection, or HDF board that compensates the tensions between the different parts and a lower plywood that provides dimensional stability.
- Slight smoothing of the wood using a brush to achieve a surface with a slight relief.
- Combination of oils and natural waxes with air drying that leave the wood with open pores. This type of oil penetrates into the wood continuously, even when it is fitted, so that it may have a 'dry' look when opened to be installed. Advantages: Easy repair of dents and scratches, very natural look, and easy maintenance with the right products. Right after installing and before its first use we recommend the use of CLEAN&GREEN AQUA OIL 1 L.
- Is suitable for installing on water radiant heating
- Material with many knots on its surface that can have different sizes depending on the type of wood. These, along with any cracks that may appear, are covered with putty.
- Made with oak wood.
- Material from a European country.
- 5 mm

PACKING

Base unit	PIECES	
Boxes	2.4 M2/BOX	
Gross weight	12.1875 KG/M2	
Net weight	11.7758 KG/M2	
Pallets	72 M2/PAL	
Sale unit	M2	
Square meters	1 M2	

