

Model: SURREY CREAM GLOSS Codes: 100285295 - L138001801

Group: G-204

Format: 15X15X0,85

RECOMMENDATIONS	
Recommended adhesive	100043280 TIXOCEM PLUS
Recommended adhesive (wet area)	100043280 TIXOCEM PLUS
Recommended joint	100236419 COLORSTUK BEIGE N
Recommended joint (wet area)	100236419 COLORSTUK BEIGE N

	DIMENSIONAL	. FEATURES
Length and width deviation	±0.5%	UNE-EN ISO 10545-2*
Orthogonality deviation	±0.5%	UNE-EN ISO 10545-2*
Side straightness deviation	±0.5%	UNE-EN ISO 10545-2*
Surface flatness deviation	+0.3%	LINE-EN ISO 10545-2*

FEATURES



* Material with surface with the ability to produce reflections.



Material suitable for use on shower walls.



Material suitable for use on indoor walls.

There are slight color changes between pied	es
---	----

	PHYSICAL PROPERTIES	
Breaking strength	≥600 N	UNE-EN ISO 10545-4*
Coefficient of linear thermal expansion	5.2 1/(10E6*°K)	ISO-10545-8*
Crack resistance	Meets	UNE-EN ISO 10545-11*
Flammability	A1	UNE-EN 13501-1*
Resistance to thermal shock	Meets	UNE-EN ISO 10545-9*
Water absorption	>10% (BIII)	UNE-EN ISO10545-3*

	CHEMICAL PROPERTIES	
Resistance to chemicals	GB	UNE-EN ISO 10545-13*
Stain resistance	Clase 3	UNE-EN ISO 10545-14*





It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A.U., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use cleaning agents containing hydrofluoric acid. In public places the tiles must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.U.

L'OC PORCELANOSA Grupo

	PACKING
Base unit	PIECES
Boxes	0.99 M2/BOX
Gross weight	14.3111 KG/M2
Net weight	14.0444 KG/M2
Pallets	74.25 M2/PAL
Sale unit	M2
Units	0.0225 M2/PIECE



