

Model: SURREY WARM GLOSS

Codes: 100285306 - L138001811

Group: G-204

Format: 15X15X0,85



RECOMMENDATIONS

Recommended adhesive	100043280 TIXOCEM PLUS
Recommended adhesive (wet area)	100043280 TIXOCEM PLUS
Recommended joint	100236419 COLORSTUK BEIGE N
Recommended joint (wet area)	100236419 COLORSTUK BEIGE N

DIMENSIONAL FEATURES

Length and width deviation	±0.5%	UNE-EN ISO 10545-2*
Orthogonality deviation	±0.5%	UNE-EN ISO 10545-2*
Side straightness deviation	±0.5%	UNE-EN ISO 10545-2*
Surface flatness deviation	±0.3%	UNE-EN ISO 10545-2*

FEATURES



Material with surface with the ability to produce reflections.



Material suitable for use on shower walls.



Material suitable for use on indoor walls.



There are slight color changes between pieces.

PHYSICAL PROPERTIES

Breaking strength	≥600 N	UNE-EN ISO 10545-4*
Coefficient of linear thermal expansion	5.2 1/(10E6*°K)	ISO-10545-8*
Crack resistance	Meets	UNE-EN ISO 10545-11*
Flammability	A1	UNE-EN 13501-1*
Resistance to thermal shock	Meets	UNE-EN ISO 10545-9*
Water absorption	>10% (BIII)	UNE-EN ISO10545-3*

CHEMICAL PROPERTIES

Resistance to chemicals	GB	UNE-EN ISO 10545-13*
Stain resistance	Clase 3	UNE-EN ISO 10545-14*



PACKING

Base unit	PIECES	
Boxes	0.99 M2/BOX	
Gross weight	14.3111 KG/M2	
Net weight	14.0444 KG/M2	
Pallets	74.25 M2/PAL	
Sale unit	M2	
Units	0.0225 M2/PIECE	

