

Model: SURREY WARM MATT
Codes: 100285330 - L138001891
Group: G-204
Format: 15X15X0,85



RECOMMENDATIONS

Recommended adhesive	100043280 TIXOCEM PLUS
Recommended adhesive (wet area)	100043280 TIXOCEM PLUS
Recommended joint	100236419 COLORSTUK BEIGE N
Recommended joint (wet area)	100236419 COLORSTUK BEIGE N

DIMENSIONAL FEATURES

Length and width deviation	±0.5%	UNE-EN ISO 10545-2*
Orthogonality deviation	±0.5%	UNE-EN ISO 10545-2*
Side straightness deviation	±0.5%	UNE-EN ISO 10545-2*
Surface flatness deviation	±0.3%	UNE-EN ISO 10545-2*

FEATURES



Gloss-free



Material suitable for use on shower walls.



Material suitable for use on indoor walls.



There are slight color changes between pieces.

PHYSICAL PROPERTIES

Breaking strength	≥600 N	UNE-EN ISO 10545-4*
Coefficient of linear thermal expansion	5.2 1/(10E6*°K)	ISO-10545-8*
Crack resistance	Meets	UNE-EN ISO 10545-11*
Flammability	A1	UNE-EN 13501-1*
Resistance to thermal shock	Meets	UNE-EN ISO 10545-9*
Water absorption	>10% (BIII)	UNE-EN ISO10545-3*

CHEMICAL PROPERTIES

Resistance to chemicals	GB	UNE-EN ISO 10545-13*
Stain resistance	Clase 3	UNE-EN ISO 10545-14*



PACKING

Base unit	PIECES	
Boxes	0.99 M2/BOX	
Gross weight	14.3111 KG/M2	
Net weight	14.0444 KG/M2	
Pallets	74.25 M2/PAL	
Sale unit	M2	
Units	0.0225 M2/PIECE	

