

Model: OXFORD BLANCO 29,4X120(A)

Codes: 100287932

Water absorption: Bla - Porcelánico (E<=0.1%)



## DIMENSIONAL FEATURES

 UNE-EN ISO 10545-2

Length	1200 MM	
Length and width deviation	Below 0.15%	+/-0.3%*
Side straightness deviation	Below 0.15%	+/-0.3%*
Squareness deviation	Below 0.15%	+/-0.3%*
Surface flatness deviation	Below 0.15%	+/-0.4%*
Thickness	11.5 MM	+/-5%*
Width	294 MM	

\*ISO-13006:2018 UNE-EN 14411:2016

## MECHANICAL FEATURES

 UNE-EN ISO 10545-4-6-7-11

Abrasion resistance	PEI 4 / 1500v	
Breaking strength	3957 N	>1300N*
Crazing resistance	Resists 3 cycles	
Modulus of rupture	57 N/MM2	>=35N/mm2*

\*ISO-13006:2018 UNE-EN 14411:2016

## HYGIENIC FEATURES

 UNE-EN ISO 10545-13-14:1995

Chemical resistance	Class "A" for swimming pools and cleaning products (resists attack). Minimum Class "B" for acids and bases	B Min.*
Stain resistance	Class 5. Easy cleaning with water	3 Min.*

\*ISO-13006:2018 UNE-EN 14411:2016

## SCOPE OF USE

Technical code-1	Use on medium traffic floors	
------------------	------------------------------	--

## ANTI-SLIP VALUE

UNE 41901:2017 EX, UNE 41902:2017 EX, DIN-51130 y ASTM C1028

Slip resistance (pendulum-wet)	CL1	
Slip resistance (ramp)	R-9	

\*ISO-13006:2018 UNE-EN 14411:2016

System Certification



**PACKING**

Boxes	1.0584 M2/BOX	
Pallets	42.3355 M2/PAL	
Units	0.3528 M2/PIECE	

## System Certification

