

Model: LINKFLOOR REALM GREECE


Codes: 100289579 - L167013402

Group: G-228

Format: 9,8X58,8X0,55



COMPOSITION



| | Size | Material | Type of material |
|---------|------|-------------|------------------------------|
| Layer 1 | 0.5 | Wear layer | Use layer with PU protection |
| Layer 2 | 0.1 | Vinyl | decorative film |
| Layer 3 | 0.7 | Elastic PVC | Intermediate comfort layer |
| Layer 4 | 3.2 | SPC | SPC composite body |
| Layer 5 | 1 | IXPE | IXPE motherboard |









CERTIFICATIONS

| | |
|--------------------------|------------|
| Floorscore certification | FLOORSCORE |
|--------------------------|------------|

ADDITIONAL NOTES

COMPOSITION: Engineered SPC Enhanced Resilient Multi-Layer Vinyl Plank / Tile

FEATURES

-  Imitates the surface of wood
-  Water-and-moisture resistant, suitable for wet areas such as bathrooms and kitchens
-  25 year warranty for domestic use valid for vinyl materials that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with ISO 10582.
-  Floor capable of dissipating excess electrical charges and distribute them over its entire surface
-  Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.
-  10 year warranty for commercial use valid for vinyl materials that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with ISO 10582.
-  Is suitable for installing on water radiant heating
-  Safety and joint durability are the main features of this easy installation system that guarantees the elimination of gaps between boards throughout the floor's lifetime. The pressure exerted between boards reinforces the union and prevents it from being carried out incorrectly.

DIMENSIONAL FEATURES

| | | |
|----------------------------|--------|-------------|
| Squareness of the item (q) | 0.07 % | ASTM F2199* |
| Straightness of face | 0.13 % | ASTM F2199* |



LABORATORY TESTS

| | | |
|---|---|------------------------|
| Abrasion resistance | CLASE T | EN660-1* |
| Acoustic insulation | (6"): IIC=51 dB;STC=54 dB/(7"): IIC=59 dB;STC=54 dB/(8"): IIC=57 dB;STC=52dB/(OWT): IIC=57 dB;STC=61 dB | ASTM E492 ; ASTM E90** |
| Castor chair effect | Sin efectos visibles | ISO 4918* |
| Commercial area class | 33 | EN 10582* |
| Critical radiant flux | 1.08 W/CM2 (CLASS I) | ASTM E648* |
| Dynamic coefficient of friction | ≥0.42 | ANSI 137.1* |
| Evaluation of propensity to accumulation of electrostatic charges | 0.5 kV | EN 14021/ EN 1815* |
| Fire resistance | Bfl-S1 | EN 13501* |
| Flexibility | PASS | ASTM F137-08(2013)* |
| Formaldehyde emissions | E1 | EN 717-2* |
| Furniture leg effect | 0.6% | ASTM F1914-07* |
| Heat resistance | 0.052 M2**K/W | EN 12667* |
| Impact resistance | PASS | EN 433* |
| Private area class | 23 | EN 10582* |
| Resistance to chemicals | PASS (CLASS 0) | ASTM F925* |
| Slip resistance (cls) | Húmedo: Clase 2/Seco: Clase 3 | UNE-ENV 12633* |
| Slip resistance (r) | R-10 | DIN 51130* |
| Thermal conductivity | 0.108 W/M**K | EN 12667* |
| Uv light fastness | 1.7 | ASTMF1515-15* |

PACKING

| | | |
|---------------|-----------------|--|
| Base unit | PIECES | |
| Boxes | 1.1525 M2/BOX | |
| Gross weight | 10.4297 KG/M2 | |
| Net weight | 9.8397 KG/M2 | |
| Pallets | 82.9786 M2/PAL | |
| Sale unit | M2 | |
| Square meters | 1 M2 | |
| Units | 0.0576 M2/PIECE | |

SPECIAL PIECES

| SAP | KEA | Description | Group | Boxes | Pallet | Units | SKU | Basic Unit | Net Weight | Gross weight |
|-----------|------------|---|-------|----------|-------------|-------------|-----|------------|------------|--------------|
| 100257147 | L167013266 | PERFIL ADH LINKFLOOR ALUMINIO 3,5X270 | G-121 | 40 ST/CS | 1000 ST/PAL | 10.58 ST/M2 | ST | ST | 0.37 KG/ST | 0.39 KG/ST |
| 100297542 | L167013456 | PERFIL ADH LINKFLOOR REALM GREECE 3,5 | G-155 | 20 ST/CS | 1000 ST/PAL | 9.26 ST/M2 | ST | ST | 0.77 KG/ST | 0.8 KG/ST |
| 100128267 | L167901793 | ZOCALO ALUMINIO 8X225 | G-121 | 12 ST/CS | 696 ST/PAL | 5.56 ST/M2 | ST | ST | 1.57 KG/ST | 1.62 KG/ST |
| 100297561 | L167013432 | ZOCALO LINKFLOOR REALM GREECE 8X220X1,5 | G-121 | 14 ST/CS | 560 ST/PAL | 5.68 ST/M2 | ST | ST | 1.33 KG/ST | 1.38 KG/ST |