

Model: AC5 HALL 1L STRAW

Codes: 100296776 - L167013421

Group: G-210

Format: 32,21X133,43X0,8

















### COMPOSITION



	Size	Material	Type of material
Layer 1	0.06	Overlay	
Layer 2	0.1	Decorative paper	
Layer 3	7.7	HDF Extreme	
Layer 4	0.14	Backside	Kraft counterbalance

### FEATURES

-  Imitates the surface of wood
-  Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.
-  25 25 year warranty for domestic use valid for laminate floors that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with EN 13329.
-  Is suitable for installing on water radiant heating
-  PanEuropean Forest Certification that guarantees to consumers the origin of the products from sustainably managed forests
-  23. Intensive residential
-  ACS Abrasion-resistance level as per Standard UNE-EN 13329
-  Gloss-free
-  5 5 year warranty for commercial use valid for laminate floors that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with EN 13329.
-  5° 5-year warranties on laminate models installed for residential use that are listed as suitable for bathrooms and kitchens.
-  Floor capable of dissipating excess electrical charges and distribute them over its entire surface
-  Safety and joint durability are the main features of this easy installation system that guarantees the elimination of gaps between boards throughout the floor's lifetime. The pressure exerted between boards reinforces the union and prevents it from being carried out incorrectly.
-  33. Intensive commercial
-  Suitable for bathroom and kitchen floors for residential use, provided that the product's installation instructions are always followed.

### DIMENSIONAL FEATURES

Uv light fastness	≥Grado 4 en escala de grises	EN 20105-A02*
-------------------	------------------------------	---------------

### LABORATORY TESTS

Acoustic insulation	$\Delta L_w=17$ dB	ISO 10140*
Density of the board	940 $\pm$ 5 KG/M3	UNE EN 323*
Fire resistance	Bfl-s1	EN 13501*
Impact resistance	CLASE IC3	EN13329 tabla 2*
Resistance to abrasion	AC5	UNE EN 13329:2000*
Resistance to staining	Grupo 1-2 $\geq$ 5/Grupo 3 $\geq$ 4	EN-438-2 / EN 13329*
Slip resistance (cls)	Húmedo: Clase 1/Seco: Clase 3	UNE-ENV 12633*
Slip resistance (dcof)	0.52	UNE EN 13893*
Swelling in thickness	$\leq$ 10%	EN 13329*
Tensile strength of joints	F $\geq$ 1 kN/ml	EN 13329*

### PACKING

Base unit	PIECES
Boxes	2.1489 M2/BOX
Gross weight	8.8371 KG/M2
Net weight	8.4183 KG/M2
Pallets	116.0401 M2/PAL
Sale unit	M2
Square meters	1 M2
Units	0.4298 M2/PIECE

### SPECIAL PIECES

SAP	KEA	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net Weight	Gross weight
100296763	L165004672	IGUALACION AC5 HALL 1L STRAW 4X270X1	G-155	20 ST/CS	1000 ST/PAL	9.26 ST/M2	ST	ST	0.7 KG/ST	0.72 KG/ST
100296765	L167013429	MAMPERLAN AC5 HALL 1L STRAW 120X7X3	G-163	2 ST/CS	200 ST/PAL	11.9 ST/M2	ST	ST	1.58 KG/ST	1.64 KG/ST
100296737	L165004675	TRANSICION AC5 HALL 1L STRAW 4X270X1	G-155	20 ST/CS	1000 ST/PAL	9.26 ST/M2	ST	ST	0.7 KG/ST	0.72 KG/ST
100296787	L165004683	ZOCALO AC5 HALL 1L STRAW 8X225X1,4	G-107	12 ST/CS	648 ST/PAL	5.56 ST/M2	ST	ST	1.57 KG/ST	1.62 KG/ST