

Model: AC4 HOME 1L TIROL

Codes: 100297732 - L165004707

Group: G-200

Format: 19,3X138,3X0,8



COMPOSITION



	Size	Material	Type of material
Layer 1	0.2	Melamine	Aminoplastic thermosetting resins
Layer 2	0.2	Decorative paper	
Layer 3	7.5	HDF	High density fibre board
Layer 4		Backside	Kraft paper sheets soaked in phenolic resins

FEATURES

-  Has a micro-structured surface similar to that of natural wood pores. It gives the material a greater wood-like feel than in the Sense version.
-  Beveled cut on all 4 edges of the board for emphasizing size.
-  Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.
-  Format where only one board has been used to finish the entire base surface.
-  Is suitable for installing on water radiant heating.
-  PanEuropean Forest Certification that guarantees to consumers the origin of the products from sustainably managed forests.
-  Safety and joint durability are the main features of this easy installation system that guarantees the elimination of gaps between boards throughout the floor's lifetime. The pressure exerted between boards reinforces the union and prevents it from being carried out incorrectly.
-  23. Intensive residential
-  32. General commercial
-  AC4 Abrasion-resistance level as per Standard UNE-EN 13329

DIMENSIONAL FEATURES

Difference in height among items	≤0.20 MM	EN 13329*
Squareness of the item (q)	≤0.20 MM	EN 13329*
Uv light fastness	≥4	EN 438-2,16*

LABORATORY TESTS

Density of the board	885 ±5 KG/M3	UNE EN 323*
Dimensional stability	≤0.90 mm	EN 13329*
Fire resistance	Cfl-s1	EN 13501*
Formaldehyde emissions	E1	DIN EN 120*
Heat resistance	R=0.078 m2 K/W M2**K/W	UNE-EN 12667:2002*
Impact resistance	IC2	EN 13329*
Resistance to abrasion	AC4	UNE EN 13329:2000*
Resistance to cigarette burns	4	EN 438*
Resistance to staining	Grado 5 (G 1 y 2) y Grado 4 (G 3)	EN 438*
Slip resistance (cls)	Clase DS	EN 13893*
Swelling in thickness	<18%	EN 13329*
Tensile strength of joints	>1.0 MPA	EN 13329*
Thermal conductivity	0.17 W/mk	DIN 52612*

PACKING

Base unit	PIECES	
Boxes	2.4023 M2/BOX	
Gross weight	7.2007 KG/M2	
Net weight	7.0246 KG/M2	
Pallets	124.9173 M2/PAL	
Sale unit	M2	
Square meters	1 M2	
Units	0.2669 M2/PIECE	

SPECIAL PIECES

SAP	KEA	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net Weight	Gross weight
100297688	L167013471	IGUALACION HOME 1L TIROL 4X270X1	G-155	20 ST/CS	1000 ST/PAL	9.26 ST/M2	ST	ST	0.7 KG/ST	0.72 KG/ST
100297728	L167013491	MAMPERLAN HOME 1L TIROL 120X7X3	G-163	2 ST/CS	200 ST/PAL	11.9 ST/M2	ST	ST	1.58 KG/ST	1.64 KG/ST
100297737	L167013475	TRANSICION HOME 1L TIROL 4X270X1	G-155	20 ST/CS	1000 ST/PAL	9.26 ST/M2	ST	ST	0.7 KG/ST	0.72 KG/ST
100297744	L167013481	ZOCALO HOME 1L TIROL 8X225X1,4	G-107	12 ST/CS	648 ST/PAL	5.56 ST/M2	ST	ST	1.57 KG/ST	1.62 KG/ST